

Application technology

Spray

# **TOP-COATS AND LUBRICANTS**

# VH300, VH301, VH302, VH315, VH353

### **Description**

Water based products, top-coats provide certain properties, that make the suitable for DELTA-PROTEKT, basecoats and zinc plating and zinc alloy plated coatings.

These top-coats are free from hazardous metals such as Cr+6 an they meet EU directives (2000/53/EC and 2002/95/CE).

### **General properties**

- No risk of hydrogen embrittlement
- Water based, inorganic components.
- Thin layer up to 3.1 microns as a maximun
- Colourless
- Good chemical resistance

Product	µtot -		
VH300			
VH301	0,09-0,14		
VH302	0,11-0,17		
VH315	0,12-0,18		
VH353	0,11-0,17		

## Standards and specs

**Dip-spinning** 

- BMW GS 90010/ ZNS3
- DAIMLER-DBL 8440/.60
- FIAT- 9.57513/ RIV/ EC 5PL
- IVECO-18-1101/ A28

# FORD VX100

- VW TL 245
- RENAULT 01-71-002-R

It is especially recomended for parts produced in high volumes, for instance, bolts and nuts.

# THIS TREATMENT IS APPLIED DIRECTLY IN LINE OR IN COMBINATION WITH PREVIOUS AND SUBSEQUENT APPLICATIONS.

GALOL S.A. offers the possibility to reduce logistic costs between the different operations of manufacturing of the part .



The information here provided must not be undestood as a legal warranty of determined properties or the adequacy for specific use



### **Corrosion protection properties**

Corrosion resistance properties acc. To ISO 9227, with more than 860h, depending on the substrate (base-coat)

allan	Minna	Mana			
Milli			mann	Manuel	R
			NAME OF COLUMN		
				U	

Parts with VH top-coat

GALOL S.A.

Camino de Montaverner, s/nº E 46850 L'Olleria (Valencia) Tel. 962 208 005 Http: www.galol.com E-mail: galol@galol.com

# VH315 V/ VH353

#### Uses